

Subject:	MAC 4.0 Driver Install	
Model	All	

Mac Driver 4.0 supports Mac OS X 10.8 and later.

A user account with administrative rights is required to perform the installation. The recommended steps are outlined below.

In some instances, the new Mac Driver 4.0 might not update the existing PPD in the system. Please follow the procedure below to resolve this issue.



Clean Printers folder (there should be no PPD's in this folder)

Before installing the new Mac driver it is important to check that your "Printers" folder is clear of older PPDs. Delete all Kyocera printers in System preferences / Devices and printers.

- 1. Double click on Macintosh HDD
- 2. Open library
- 3. Open printers.
- 4. Delete all the Kyocera .PPDs in this folder. (DO NOT delete any folders)

After downloading MacPhase4.0_2017.10.18 driver, double click on the .zip file. Double click on the extracted folder.

🔇 КЧОСЕRА

Release Notes

Package Installer Setup

You can install the driver using the provided package installer.

- 1. Double-click the .DMG file to run the installer.
- 2. In the installer dialog, click Continue to proceed to the readme page.



3. Click Continue to proceed to the license agreement page.





4. Review the Software License Agreement, and then click Continue.



5. Click Agree to accept the terms of the license agreement.

000		🤿 Install	Kyocera Macintosh			
3	To continue i of the softwa	installing the source license agre	oftware you must ement.	agree to the ter	ms	
⊖ Int						
🖯 Rea	Click Agree to continue or click Disagree to cancel the installation					
🖯 Lic	and quit the Installer.					
Des	Read Lice	nse	Disagr	ee Agre	e)	
Ins						
 Install Summ 	hary	exclusive, non-tran included in this pay storing, loading, in You may r a) modify, derivat Softwa b) rent, tra person c) remove d) Post the genera web sit	sterable license to use ackage (all referred to hei stalling, executing or displ not: translate, reverse englin- ive works based on, or co re; inster or grant any rights without the prior written c any proprietary notices, lai s Software to any location i public, including, but not ies, and ftp sites.	the Software and reli ein as the "Software") aying the Software. aying the Software in py (except for the bac in the Software in an onsent of KYOCERA; bels or marks on the So that is electronically act limited to: electronic b	ated materials "Use" means emble, create kup copy) the y form to any oftware; pessible to the ulletin boards,	
© 2017 KYOC KYOCERA Doo	ERA Corporation, cument Solutions Inc.	Print	Save	Go Back	Continue	



 Click Install and enter the admin password to complete the standard installation. Alternatively, you can select Customize to perform a custom installation. For custom installation, select the Print Option Pane checkbox to install the Print Option Pane.



7. Click **Close** to exit when the installation is complete.





Adding Printers

After you install the driver, you can add the printers to be used on the system.

1. Open **System Preferences** and click **Printers and Scanners (**this may also be called Print & Scan or Print & Fax), depending on the Mac OS X version you are using).



2. In the Printers & Scanners dialog, you can click the "+" icon at the bottom of the Printers list to open the Add Printer dialog (this may also be called Add, depending on the Mac OS X version you are using).

	Printers & Scanners	Q Search
Kyocera TASKalfa 552 Idle Kyocera TASKalfa 555 Idle Kyocera TASKalfa 605 Idle Kyocera TASKalfa 655 Idle Kyocera TASKalfa 705 Idle Kyocera TASKalfa 705 Idle Kyocera TASKalfa 705 Idle Kyocera TASKalfa 755 Idle Kyocera TASKalfa 755 Idle Kyocera TASKalfa 755 Idle Kyocera TASKalfa 755 Idle	Print Sca Kyocera TASKa Open Print C Options & Su Location: Kind: Kyocera TASKalfa Status: Idle	an Ilfa 7551ci Queue pplies 7551ci (KPDL) C Sharing Preferences
	Default printer: 4.4.4.4 Default paper size: US Letter	• ?



To add a printer, you must first choose a connection type—Bonjour, IP Printer, or Windows. If you choose the Default connection type, Printer Setup Utility displays a list of all available printers with Bonjour support. When you select a printer to add to the printers list, Printer Setup Utility retrieves the selected printer's address, icon, and model information. Printer Setup Utility then uses this information to create a new printer queue, and then adds the printer to the list when you click Add.

	۳ 🛱 🤍		
ult Fax	IP Windows	Search	
Printer Name		▲ Kind	
10.10.11.124 @	Kevin's Mac mini	Bonjour Shared	
0-30C-KMC-3	60E	Bonjour	
50-30C-KMC-3	610	Bonjour	
np color LaserJe	t 4600 [E66F1D]	Bonjour	
IP Color LaserJe	et CP3525 [894A69]	Bonjour	
IP Color LaserJe	et CP4005 PS @ YASUHIDE-XP-760.ktd.com	Bonjour Shared	
M1901DD		Bonjour	
MI9FFD2		Bonjour	
Name:	No Selection		
Location:	No Selection		
Print Using:			* *

For better printing support, it is recommended to use Line Printer Daemon (LPD) for the protocol. To add an LPR printer that uses IP, enter the printer's DNS host name or IP address and then select the appropriate model from the Print Using menu. The matching PPD for the printer is automatically selected by the OS.

000		Add Printer		\bigcirc
	۵ 🚔	٩		
Default Fax	IP Windows		Search	
Protocol:	Line Printer Daemon - LPD		;	9
Address:			,	•
	Enter host name or IP address.			
Queue:			,	9
	Leave blank for default queue.			
News	No Colontino			
Name:	No Selection			
Location:	No Selection			
Print Using:			4 7	
			Add	

3. Click Add.